

## Used Pump Information

T: 01953 454540 F: 01953 456968

E: enquiries@stuartgroup.info

W: www.stuartgroup.ltd.uk

Stuart House, Hargham Road, Shropham, Norfolk, NR17 1DT

### SURFACE PUMP DATA INFORMATION

| PUMP TYPE                          | FIRE | X                         | CONTRACTOR   | INDUSTRIAL                              | TRADE      |
|------------------------------------|------|---------------------------|--|---|------------|
| Stock No                           |      | XSP9828                   |  | Retail Price                            | £14,000-00 |
| Manufacturer                       |      | SELWWOD                   |  | Date In Stock                           | AUG 2024   |
| Model                              |      | S200                      |  | Year of Manufacture                     | 2008       |
| Serial No                          |      | 131D                      |  | <b>CHASSIS</b>                          |            |
| <b>PUMP DATA</b>                   |      |                           | Open/ Skid   | SKID                                    |            |
| Max Flow                           |      | 540M3/HR                  | Sound Attenuated   | YES HUSHPACK                            |            |
| Max Head                           |      | 18.5M                     | Length   | 2.8M (APPROX)                           |            |
| Suction Size - mm                  |      | 8" / 203mm                | Width  | 1.6M (APPROX)                           |            |
| Suction Coupling Type              |      | FEMALE BAUER              | Height   | 2.1M (APPROX)                           |            |
| Discharge Size - mm                |      | 8" / 203mm                | Colour   | YELLOW/BLACK                            |            |
| Discharge coupling Type            |      | MALE BAUER                | Condition  | USED                                    |            |
| Discharge Detail<br>NRV/Gate/Gauge |      | DISCHARGE NRV – FLAP TYPE |  |   |            |
| Shaft Seal – Mech /Packing         |      | MECHANICAL SEAL           |  | <b>LIFTING DATA/ CHASSIS</b>            |            |
| Pump Speed Min/Max                 |      | 1600 RPM MAX              | Weight Kg  | 2340 KG (DRY)                           |            |
| Impeller Type – Open/Closed        |      | OPEN                      | Centre Point   | YES                                     |            |
| Impeller Size                      |      | 235MM                     | Corner   | -                                       |            |
| Solids Handling                    |      | 100MM                     |  |   |            |
| Others – Stages                    |      | SINGLE                    | Forklift   | YES                                     |            |
| Material                           |      | CAST IRON                 | Trailer – Road tow   | -                                       |            |
| Priming Type Comp/vac/ventr        |      | VAC DIAPHRAGM (SELFPRIME) | Trailer – Site tow   | -                                       |            |
| Long/Close Coupled Pump            |      | LONG                      | Tow Bar Type   | -                                       |            |
| Belt Drive                         |      | NO                        |  |   |            |
|                                    |      |                           | <b>FUEL TANK DATA</b>  |   |            |
| <b>ENGINE DATA</b>                 |      |                           | Size - Dimensions  | -                                       |            |
| Manufacturer                       |      | ISUZU                     | Capacity   | 300 LITRES                              |            |
| Model                              |      |                           | Gauge  | YES                                     |            |
| Serial No                          |      | -                         | Bunded   | YES INTEGRAL                            |            |
| Hours                              |      | 493                       | Chassis  | -                                       |            |
| Exhaust Type                       |      | SILENCED                  | Free Standing  | -                                       |            |
| Bellows                            |      | YES (EXHAUST)             | Special  | -                                       |            |
| Voltage                            |      | 12V                       | <b>STARTER PANEL</b>   |   |            |
| Battery Type                       |      | LEAD ACID WITH ISOLATOR   | Key / Button   | KEY                                     |            |
| Battery Isolator                   |      | YES                       | Hour Meter   | YES – (493 Hrs)                         |            |
| Water Jacket Heater KW             |      | NO                        | Oil Pressure   | LED                                     |            |
| Cooling – Air – Rad - Exc          |      | RADIATOR                  | Water Temp   | LED                                     |            |
| <b>ELECTRIC MOTOR</b>              |      |                           | Water Pressure   | NO                                      |            |
| Make                               |      | -                         | Water Vacuum   | NO                                      |            |
| Voltage                            |      | -                         | Rev Counter  | NO                                      |            |
| KW                                 |      | -                         | Special  | FLOAT SWITCH.<br>AUTO STOP/START FITTED |            |
| Amps                               |      | -                         | <b>Additional Comments.</b>  |   |            |
| Cooling                            |      | -                         | EMERGENCY STOP FITTED BOTH SIDES.  |   |            |
| Speed                              |      | -                         | BATTERY ISOLLATOR FITTED.  |   |            |
| Foot / Flange                      |      | -                         | OFFERED WITH A RETURN TO BASE WARRANTY OF 30-DAYS<br>OR 250 HOURS WHICHEVER FIRST. |   |            |
| Starter Type                       |      | -                         |  |   |            |